

50/125 OM2 Multimode Simplex Pigtail 3.0mm

Custom Labeling Available

Other Connector Combinations Available

Boot Options:

- - Short Boots
- - Bendable Boots
- - *45° Boots
- - *90° Boots

Plenum cable available upon request

2mm cables available

*Not available for all boots



SC Multimode Simplex

Cable & Connector Specifications:	
Fiber Type	50/125 OM2 Multimode
Insertion Loss Per Connector	< 0.3dB, Typical 0.25dB
Return Loss VS. Polish Type	UPC: > 50dB, Typical 55dB APC: > 60dB, Typical 65dB
Apex Offset	< 50µm
Fiber Height	< 100nm
Repeatability	> 500 Cycles
Operating Temperature	-40°C To +75°C
Humidity Range	5% To 95% (Non-Condensing)
Strain Relief Boot Lengths	2.2cm to 3.5cm Available

50/125 OM2 Multimode Simplex Pigtail 3.0mm		
LC-Pigtail Simplex	F9G11C1GCL0XXX	Specify Length When Ordering
SC-Pigtail Simplex	F9G11C1GC60XXX	Specify Length When Ordering
FC-Pigtail Simplex	F9G11C1GC70XXX	Specify Length When Ordering
ST-Pigtail Simplex	F9G11C1GC10XXX	Specify Length When Ordering

Other Connector Combinations available.