


[Back to SFP Page](#)

GE-SX-MM:	FDN-GE-SX-MM SFP
Cisco® Compliant Ethernet Transceiver	
1.25GB Gigabit Ethernet / 1.063GB Fiber Channel	
Application: This 100% Cisco® Compliant 1000Base SX SFP 1310nm Transceiver with DOM and extended temperature, is hot-swappable and designed to plug directly into your SFP/Mini-GBIC interface slot in your router and switch for Ethernet and Fiber Channel network interface applications.	
Reach	550m
Fiber Type	MMF 50µm, MMF 62.5µm
Fiber Optic Connector	LC
Center Wavelength	850nm
Min TX Power	-9.5 dBm
Max TX Power	0 dBm
RX Sensitivity	-18 dBm
Max Input Power	-1 dBm
Link Budget	8.50 dB
Dimensions	MSA SFP Standard Height: 0.33" (8.5 mm) Width: 0.52" (13.4 mm) Depth: 2.18" (55.5 mm)
Power	3.3V
Operating Temperature	-5°C - 85°C
Standards	IEEE: 802.3 2003; ANSI X3.297-1997
Compliance	IEC-60825; FDA-21; CFR 1040.10; CFR 1040.11
Warranty	1 Year Full Replacement

Cisco® is a registered trademark of Cisco Systems, Inc.