

Custom Labeling Available

Other Connector Combinations Available

Boot Options:

- Short Boots
- Bendable Boots
- *45° Boots
- *90° Boots
- Uni-Boots available for LCs

LC & SC connectors available with or without duplex clips/yokes

Plenum cable available upon request

[2mm cables available](#)

***Not available on all boots**



Singlemode Duplex SC Yoked LC Clipped

Cable & Connector Specifications:	
Fiber Type	Singlemode OS2 (SMF-28)
Insertion Loss Per	< 0.3dB, Typical 0.25dB
Return Loss VS. Polish Type	UPC: > 50dB, Typical 55dB APC: > 60dB, Typical 65dB
Apex Offset	< 50µm
Fiber Height	< 100nm
Repeatability	> 500 Cycles
Operating Temperature	-40°C To +75°C
Humidity Range	5% To 95% (Non-Condensing)
Strain Relief Boot Lengths	2.2cm to 3.5cm Available

Singlemode Duplex OS2 3.0mm Riser Cables		
SC/UPC-SC/UPC	F9C21A1GCYYXXXM	Specify Length When Ordering
SC/UPC-SC/APC	F9C21A1GCYWXXXM	Specify Length When Ordering
SC/UPC-FC/UPC	F9C21A1GCY7XXXM	Specify Length When Ordering
SC/UPC-ST/UPC	F9C21A1GCY1XXXM	Specify Length When Ordering
SC/APC-SC/APC	F9C21A1GCWWXXXM	Specify Length When Ordering
SC/APC-FC/UPC	F9C21A1GCW7XXXM	Specify Length When Ordering
SC/APC-FC/APC	F9C21A1GCWAXXXM	Specify Length When Ordering
SC/APC-ST/UPC	F9C21A1GCW1XXXM	Specify Length When Ordering
LC/UPC-LC/UPC	F9C21A1GCCCXXXM	Specify Length When Ordering
LC/UPC-SC/UPC	F9C21A1GCCYXXXM	Specify Length When Ordering
LC/UPC-SC/APC	F9C21A1GCCWXXXM	Specify Length When Ordering
LC/APC-LC/APC	F9C21A1GCGFXXXM	Specify Length When Ordering
LC/APC-SC/UPC	F9C21A1GCFYXXXM	Specify Length When Ordering
LC/APC-SC/APC	F9C21A1GCFWXXXM	Specify Length When Ordering
FC/UPC-FC/UPC	F9C21A1GC77XXXM	Specify Length When Ordering
FC/UPC-FC/APC	F9C21A1GCA7XXXM	Specify Length When Ordering
FC/APC-FC/APC	F9C21A1GCAYXXXM	Specify Length When Ordering
FC/APC-SC/UPC	F9C21A1GCA6XXXM	Specify Length When Ordering
FC/APC-ST/UPC	F9C21A1GCA1XXXM	Specify Length When Ordering
ST/UPC-ST/UPC	F9C21A1GC11XXXM	Specify Length When Ordering

Other Connector Combinations available.