

Singlemode Simplex OS2 MU 2.0mm Riser Assemblies

Other Connector Combinations available

Short Boots Available

Custom Labeling Available

Cable & Connector Specifications:	
Fiber Type	Singlemode OS2 (SMF-28)
Insertion Loss (Transmit)	< 0.8dB
Insertion Loss (Receive)	< 0.3dB (0.25dB Typical)
Return Loss	> 50dB (55dB Typical)
Radius of Curvature	7 to 25mm
Apex Offset	< 50µm
Fiber Height	< 100nm
Repeatability	> 500 Cycles
Operating Temperature	-40°C To +75°C
Humidity Range	5% To 95% (Non-Condensing)

Singlemode Simplex OS2 MU 2.0mm Riser Assemblies		
MU/UPC-MU/UPC	F9C11A2GCUUXXX	Specify Length When Ordering
MU/UPC-LC/UPC	F9C11A2GCULXXX	Specify Length When Ordering
MU/UPC-SC/UPC	F9C11A2GCU6XXX	Specify Length When Ordering
MU/UPC-SC/APC	F9C11A2GCUBXXX	Specify Length When Ordering
MU/UPC-FC/UPC	F9C11A2GCU7XXX	Specify Length When Ordering
MU/UPC-FC/APC	F9C11A2GCUAXXX	Specify Length When Ordering
MU/UPC-ST/UPC	F9C11A2GCU1XXX	Specify Length When Ordering